

PIVOTING DESK LEDI® 1/60/S



Clock designed for quiet environments radio/TV studios

- Legibility 5 meters
- Highly luminescent 7-segment LED display: hour, minute
- Height of digits: Hour/minutes = 18 mm ; seconds = 8mm
- Seconds: 7-segment digits + Wave 60 dots ø 80 mm
- Minimum 2-day power reserve in case of power failure by built-in Ni-Mh battery
- Power supply: 230VAC 50/60Hz external. Class 1
- Operating range: -20 to 70°C
- Pivoting casing to be placed on a desk
- Dimensions: 130x145x190 mm
- Manual brightness adjustment
- In accordance with CE

ITEM CODE

3126 /

CASING		↑	↑	↑	↑	↑
Single-sided on desk	■	1				
Double-sided on desk	■	2				
VERSION						
Standalone: radio-synchronisable quartz time base 3.6864 MHz Holdover +/- 0.1 sec/24 h (between 20 and 30°C)	■	2				
6mA/24V reversed parallel minute pulses receiver clock	■	3				
Serial reversed 1/2 minute pulses receiver clock	■	5				
Consumption 1.25V. 60 to 120mA. 39 ohms shunt						
⁽¹⁾ Réceptrice AFNOR NFS 87500	■	8				
SMPTE-EBU Receiver	■	7				
⁽²⁾ ASCII RS232 Receiver	■	B				
⁽²⁾ ASCII RS422-485 Receiver	■	Q				
DCF Radiosynchronisation. DCF Antenna + 4m cable	■	D				
<i>(1) If IRIG.B. version, please specify as a note on your order</i>						
LED						
Red	■		1			
Green	■		2			
POWER SUPPLY						
Standard: 230VAC 50/60Hz	■			0		
OPTION						
Timer casing + 2 m cable (count up/down/intermediate time)	■					C
⁽²⁾ ASCII RS232 output	■					A
or: ⁽²⁾ ASCII RS422-485 output	■					R
Tropicalization	■					U

(2) Only one ASCII output or one ASCII input possible